

Amendments to the Claims:

The text of all pending claims, (including withdrawn claims) is set forth below. Canceled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strike through~~. The status of each claim is indicated with one of (original), (currently amended), (canceled), (withdrawn), (new), (previously presented), or (not entered).

Applicant reserves the right to pursue any canceled claims at a later date.

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1.-7. (cancelled)

8. (previously presented) A remote control for wirelessly issuing commands to a remotely controllable device, comprising:

a control unit for executing an assignment mode prior to startup of the remote control;  
and

a rechargeable battery for providing a power supply to the remote control, wherein  
the remote control is configured to be temporarily and removably fixed to a docking point arranged at the remotely controllable device;

the rechargeable battery is configured to be charged by the remotely controllable device via an inductive power interface when the remote control is fixed to the docking point; and

the docking point is configured to transmit information to the remote control, the information configured at least for triggering execution of the assignment mode on the remote control.

9. (previously presented) The remote control according to claim 8, wherein the power interface comprises:

a first transformer part fixed-mounted to the remotely controllable device having at least one first coil; and

a second transformer part fixed-mounted to the remote control having at least one second coil, wherein the first and second transformer parts form a transformer when the remote control is docked at the docking point.

10. (previously presented) The remote control according to claim 8, wherein the remote control is configured to be fixed to the remotely controllable device using a magnetic mounting holder arranged at the remotely controllable device.

11. (previously presented) The remote control according to claim 9, wherein the first and second transformer parts each comprise a core with at least one of the cores including a permanent magnet.

12. (previously presented) The remote control according to claim 9, wherein the transformer is configured to transmit information related to the assignment mode.

13. (previously presented) The remote control according to claim 9, wherein the transformer is configured to transmit information related to an initialization mode.

14. (previously presented) The remote control according to claim 13, wherein the initialization mode is configured to trigger the execution of the assignment mode.

15. (previously presented) The remote control according to claim 9, wherein the second coil is configured to carry an electrical load of a controllable impedance, the controllable impedance configured to be switched by a specific frequency.

16. (previously presented) The remote control according to claim 15, wherein the first coil is arranged in a first electric circuit, the first electric circuit comprising a filter tuned to the specific frequency.

17. (previously presented) A wireless remote control system, comprising:  
a remote control having a control unit, the control unit configured to execute an assignment mode prior to startup of the remote control;  
the remotely controllable device;  
a rechargeable battery for providing a power supply to the remote control;  
a docking point arranged at the remotely controllable device for temporarily and removably supporting the remote control; and  
an inductive power interface for charging the rechargeable battery when the remote control is docked at the docking point, wherein the docking point is configured to transmit information to the remote control, the information configured at least for triggering execution of the assignment mode on the remote control.

18. (previously presented) The remote control system according to claim 17, wherein the power interface comprises:  
a first transformer part fixed-mounted to the remotely controllable device having at least one first coil; and  
a second transformer part fixed-mounted to the remote control having at least one second coil, wherein the first and second transformer parts form a transformer when the remote control is docked at the docking point.

19. (previously presented) The remote control system according to claim 18, wherein the second coil is configured to carry an electrical load of a controllable impedance, the controllable impedance configured to be switched by a specific frequency.

20. (previously presented) The remote control system according to claim 19, wherein the first coil is arranged in a first electric circuit, the first electric circuit comprising a filter tuned to the specific frequency.